


MIXPAC™ STATOMIX MS- AND ME-SERIES



Product Description:

- MS 08-XXY and MS 10-XXY
- ME 08-XXY and ME 10-XXY



XX= Number of mixing elements
Y= Outlet Type

Feature	Description	Product Parameters	Visualisation
Diameter	<ul style="list-style-type: none"> • Nominal diameter of the mixing element. • Defines the flow resistance and shear rate. 	<ul style="list-style-type: none"> • MS 08-XXY: 8 mm • ME 08-XXY: 8 mm • MS 10-XXY: 10 mm • ME 10-XXY: 10 mm 	
Inlet	<ul style="list-style-type: none"> • Bell Inlet geometry compatible with majority of semi-automatic and automatic Meter Mix (MMD) equipment 	<ul style="list-style-type: none"> • Bell Inlet I. D.: • MS: 16.7 mm • ME: 15.9 mm 	
	<ul style="list-style-type: none"> • Adapter ring for MS to ME conversion 	<ul style="list-style-type: none"> • AD 17-16 (101489) 	
Outlet	<ul style="list-style-type: none"> • Variety of mixer outlet geometries can help to obtain the desired dispensing pattern. • Depending on the mixer family and type, the following outlets can be provided: <ul style="list-style-type: none"> • Stepped (T) • Threaded (G) • Straight (D) • Luer (L) • Using Luer Lock adapters, different mixing needles could be used for precise dispensing operations. 	<ul style="list-style-type: none"> • MS 08-XXY & ME 08-XXY • Stepped (T) • O. D.: 2.4 mm • MS 10-XXY & ME 10-XXY • Stepped (T) • O. D.: 3 mm • MS 08-XXY & ME 08-XXY • LA 06-08 (102357) • MS 10-XXY & ME 10-XXY • LA 10-00 (102358) 	
Elements	<ul style="list-style-type: none"> • Number of mixing elements directly affects the mixing quality. • The number of layered A/B adhesive components are calculated as 2n layers for n number of mixing elements. • Machine mixer elements are subjected to higher mechanical loads and therefore need to be made of polymers with superior mechanical properties. 	<ul style="list-style-type: none"> • MS 08-XXY & MS 10-XXY • 18, 24, 32 elements • Yellow • Polyacetal (POM) • ME 08-XXY & ME 10-XXY • 24, 32 elements • Blue • Polyacetal (POM) • Polyacetal (POM) elements ensure higher pressure resistance and longer operation at elevated Temperatures. 	

MIXER SPECIFIC PROPERTIES



Feature	Description	Product Parameters	Visualisation
Waste Volume	<ul style="list-style-type: none"> Waste volume is defined as the remaining liquid inside the mixer housing after the usage. Waste volume is calculated as the total volume trapped between the two indicated limits. 	<ul style="list-style-type: none"> MS 08-18T: 6.3 mL MS 08-24T: 8.2 mL MS 08-32T: 12.4 mL MS 10-18T: 12.6 mL MS 10-24T: 16.3 mL MS 10-32T: 21.0 mL ME 08-24T: 8.2 mL ME 08-32T: 10.5 mL ME 10-24T: 16.1 mL ME 10-32T: 20.7 mL 	
Maximum operating pressure ⁽¹⁾	<ul style="list-style-type: none"> The values show the maximum allowed pressure under which the mixers can be used ⁽¹⁾⁽²⁾ 	<p>At Room Temperature:</p> <ul style="list-style-type: none"> MS 08-18T: 50 bar/725 psi MS 08-24T: 50 bar/725 psi MS 08-32T: 50 bar/725 psi MS 10-18T: 47 bar/680 psi MS 10-24T: 47 bar/680 psi MS 10-32T: 47 bar/680 psi ME 08-24T: 50 bar/725 psi ME 08-32T: 50 bar/725 psi ME 10-24T: 47 bar/680 psi ME 10-32T: 47 bar/680 psi <p>At 40 °C:</p> <ul style="list-style-type: none"> MS 08-18T: 42 bar/609 psi MS 08-24T: 42 bar/609 psi MS 08-32T: 42 bar/609 psi MS 10-18T: 33 bar/479 psi MS 10-24T: 33 bar/479 psi MS 10-32T: 33 bar/479 psi ME 08-24T: 42 bar/609 psi ME 08-32T: 42 bar/609 psi ME 10-24T: 33 bar/479 psi ME 10-32T: 33 bar/479 psi 	

⁽¹⁾ Compatibility with the dispensed fluid and usage conditions must be verified for the specific customer application.

⁽²⁾ High quality and matching safety shrouds are available for use with Statomix™ type ME & MS mixers. More detailed information can be requested from your local sales representative.

IMPORTANT: For health and safety reasons, shrouds must be used at all times.

All the trademarks mentioned here are trademarks of medmix AG. Copyright © medmix Switzerland AG 202[3]

Seller is not responsible or liable for the design of the customer's products. It is the customer's responsibility to determine that its product is safe, complies with applicable laws and regulations and that its product is fit for its intended use.

DELIVERING INNOVATION. INSPIRING CONFIDENCE.

EUROPE

medmix Switzerland AG

Ruetistrasse 7
9469 Haag, Switzerland
Phone +41 81 414 70 00
sales.industry@medmix.com
www.medmix.swiss

USA, SOUTH AMERICA, CANADA AND MEXICO

medmix US Inc.

8 Willow St.
Salem, NH 03079, USA
Phone +1 603 893 2727
sales.industry@medmix.com
www.medmix.swiss

UK AND IRELAND

medmix UK Ltd.

1 Tealgate, Charnham Park, Hungerford
Berkshire, RG17 0YT, United Kingdom
Phone: +44 (0)1488 647 800
sales.industry@medmix.com
www.coxdispensers.com

SPAIN

medmix Spain S.L.

Av. Puerto de Alicante, 5-2
46394 Riba-roja de Túria
Valencia, Spain
sales.spain@medmix.com
www.medmix.swiss

ASIA PACIFIC

medmix China Ltd.

68 Bei Dou Lu, Minhang Shanghai
200245, China
Phone: +86 21 6430 68 68
sales.industry@medmix.com
www.medmix.swiss



Legal Notice: This brochure is a general presentation. The information contained in this publication is believed to be accurate and reliable but is not to be construed as implying any warranty or guarantee of performance. We waive any liability and indemnity for effects resulting from its application. Please, contact us for a description of the warranties and guarantees offered with our products. Directions for use and safety will be given separately. All information herein is subject to change without notice.

© 2024 medmix Switzerland AG All rights reserved.

medmix is a trademark belonging to medmix AG, and COX, MK and MIXPAC are trademarks belonging to medmix Switzerland AG.